

**CHAPTER 20**  
**FLOODPLAIN ZONING ORDINANCE**

STATUTORY AUTHORIZATION, FINDING OF FACT, STATEMENT  
OF PURPOSE, TITLE AND GENERAL PROVISIONS

- 20.01 Statutory Authorization
- 20.02 Finding of Fact
- 20.03 Statement of Purpose
- 20.04 Title
- 20.05 General Provisions
  - (1) Areas to be Regulated
  - (2) Official Maps and Revisions
  - (3) Establishment of Districts
  - (4) Locating Floodplain Boundaries
  - (5) Removal of Lands from Floodplain
  - (6) Compliance
  - (7) Municipalities and State Agencies Regulated
  - (8) Abrogation and Greater Restrictions
  - (9) Interpretation
  - (10) Warning and Disclaimer of Liability
  - (11) Severability
  - (12) Annexed Areas for Cities/Villages
  - (13) General Development Standards

GENERAL STANDARDS APPLICABLE TO ALL FLOODPLAIN DISTRICTS

- 20.07 Hydraulic and Hydrologic Analyses
- 20.08 Watercourse Alterations
- 20.09 Chapter 30, 31, Wis. Stats., Development
- 20.10 Public or Private Campgrounds

FLOODWAY DISTRICT (FW)

- 20.12 Applicability
- 20.13 Permitted Uses
- 20.14 Standards for Development
- 20.15 Prohibited Uses

FLOODFRINGE DISTRICT (FF)

- 20.17 Applicability
- 20.18 Permitted Uses
- 20.19 Standards for Development

## GENERAL FLOODPLAIN DISTRICT (GFP)

- 20.21 Applicability
- 20.22 Permitted Uses
- 20.23 Standards for Development
- 20.24 Determining Floodway/Floodfringe Limits

## NONCONFORMING USES

- 20.26 General
- 20.27 Floodway Areas
- 20.28 Floodfringe Areas

## ADMINISTRATION

- 20.30 Zoning Administrator
- 20.31 Zoning Agency
- 20.32 Board of Adjustment/Appeals
- 20.33 To Review Appeals of Permit Denials
- 20.34 Flood proofing
- 20.35 Public Information

## AMENDMENTS

- 20.37 General
- 20.38 Procedures

## ENFORCEMENT AND PENALTIES

## DEFINITIONS

**Statutory Authorization, Finding of Fact, Statement of Purpose, Title and  
General Provisions**

**20.00 STATUTORY AUTHORIZATION, FINDING OF FACT, STATEMENT OF PURPOSE,  
TITLE AND GENERAL PROVISIONS**

**20.01 STATUTORY AUTHORIZATION**

This ordinance is adopted pursuant to the authorization in ss. 61.35 and 62.23, for villages and cities; 59.69, 59.692, and 59.694 for counties; and the requirements in s. 87.30, Stats.

**20.02 FINDING OF FACT**

Uncontrolled development and use of the floodplains and rivers of this municipality would impair the public health, safety, convenience, general welfare and tax base.

**20.03 STATEMENT OF PURPOSE**

This ordinance is intended to regulate floodplain development to:

- (1) Protect life, health and property;
- (2) Minimize expenditures of public funds for flood control projects;
- (3) Minimize rescue and relief efforts undertaken at the expense of the taxpayers;
- (4) Minimize business interruptions and other economic disruptions;
- (5) Minimize damage to public facilities in the floodplain;
- (6) Minimize the occurrence of future flood blight areas in the floodplain;
- (7) Discourage the victimization of unwary land and homebuyers;

- (8) Prevent increases in flood heights that could increase flood damage and result in conflicts between property owners; and
- (9) Discourage development in a floodplain if there is any practicable alternative to locate the activity, use or structure outside of the floodplain.

**20.04 TITLE**

This ordinance shall be known as the Floodplain Zoning Ordinance for Jackson County, Wisconsin.

**20.05 GENERAL PROVISIONS**

(1) **AREAS TO BE REGULATED**

This ordinance regulates all unincorporated areas that would be covered by the regional flood or base flood as shown on the Flood Insurance Rate Map (FIRM) or other maps approved by the WI-DNR. Base flood elevations are derived from the flood profiles in the Flood Insurance Study (FIS) and are shown as AE, A1-30, and AH zones on the FIRM. Other regulatory zones are displayed as A and AO zones. Regional Flood Elevations (RFE) may be derived from other studies. If more than one map or revision is referenced, the most restrictive information shall apply.

(2) **OFFICIAL MAPS AND REVISIONS**

The boundaries of all floodplain districts are designated as A, AE, AH, AD or A1-30 on the maps based on the Flood Insurance Study (FIS) listed below. Any changes to the base flood elevations (BFE) or any changes to the boundaries of the floodplain or floodway in the FIS or on the Flood Insurance Rate Map (FIRM) must be reviewed and approved by the DNR and FEMA through the Letter of Map Changes process (see 20.36 Amendments) before it is effective. No changes to the RFE's on non-FEMA maps shall be effective until approved by the DNR. These maps and revisions are on file in the Office of the Zoning Administrator, Jackson County. If more than one map or revision is referenced the most restrictive information shall apply.

- (a) **OFFICIAL MAPS.** Based on the FIS:  
Flood Insurance Rate Map (FIRM) panel numbers

FLOODPLAIN ZONING CODE 20.05(2)(a)

55053C0008C, 55053C0009C, 55053C0020C, 55053C0028C,  
55053C0029C, 55053C0045C, 55053C0065C, 55053C0070C,  
55053C0090C, 55053C0110C, 55053C0120C, 55053C0130C,  
55053C0135C, 55053C0140C, 55053C0143C, 55053C0144C,  
55053C0145C, 55053C0155C, 55053C0160C, 55053C0163C,  
55053C0165C, 55053C0170C, 55053C0180C, 55053C0190C,  
55053C0194C, 55053C0195C, 55053C0211C, 55053C0212C,  
55053C0213C, 55053C0214C, 55053C0220C, 55053C0240C,  
55053C0245C, 55053C0261C, 55053C0263C, 55053C0264C,  
55053C0268C, 55053C0269C, 55053C0308C, 55053C0309C,  
55053C0316C, 55053C0317C, 55053C0326C, 55053C0327C,  
55053C0328C, 55053C0329C, 55053C0331C, 55053C0332C,  
55053C0335C, 55053C0340C, 55053C0345C, 55053C0355C,  
55053C0360C, 55053C0369C, 55053C0379C, 55053C0383C,  
55053C0385C, 55053C0386C, 55053C0387C, 55053C0388C,  
55053C0389C, 55053C0395C, 55053C0405C, 55053C0410C,  
55053C0415C, 55053C0420C, 55053C0430C, 55053C0435C,  
55053C0452C, 55053C0456C, 55053C0457C, 55053C0476C,  
55053C0477C, 55053C0510C, 55053C0530C, 55053C0540C,  
55053C0545C, 55053C0555C, 55053C0557C, 55053C0559C,

Dated September 28, 2012; with corresponding profiles that are based on the Flood Insurance Study (FIS) dated September 28, 2012, Volume Number 55053CV000A, for the Unincorporated Areas of Jackson County (550583).

- (b) OFFICIAL MAPS: Based on other studies. Any maps referenced in this section must be approved by the DNR and be more restrictive than those based on the FIS of the site of the proposed development.
1. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the Trow Lake Dam on Halls Creek, dated November 25, 1985, Donahue & Associates, Approved by WI-DNR.
  2. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the Millston Dam on Wyman Creek, dated September of 1996, Ayres & Associates, Approved by WI-DNR.
  3. The Dam Hazard Assessment and the 100 year Hydraulic Shadow Maps for the Oakwood Lake Dam on Halls Creek, dated February of 1998, MSA, Approved by WI-DNR.

FLOODPLAIN ZONING CODE 20.05(2) (b)

4. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the May Coulee Dam, dated December of 2005, Tiry Engineering, Approved by WI-DNR.
5. The Dam Hazard Rating Study and 100 year Hydraulic Shadow Maps for the Sherwood Dam on Hay Creek, dated October of 1998, Ayres and Associates, Approved by the WI-DNR, March 16, 2000.
6. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the Melrose Mill Pond Dam on Douglas Creek, dated December of 2011, Ayres & Associates, and Approved by the WI-DNR, August 17, 2012.
7. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the East Seventeen Flowage Dam Resettlement Admin 12 for unnamed tributary to Morrison Creek, dated February 28, 2013, Cedar Corporation, Approved by the WI-DNR, July 8, 2013.
8. The Dam Hazard Rating Study and the 100 year Hydraulic Shadow Maps for the West Seventeen Flowage Dam Resettlement Admin 17 for unnamed tributary to Morrison Creek, dated March 1, 2013, Cedar Corporation, Approved by the WI-DNR, July 8, 2013.
9. The Dam Hazard Assessment and the 100 year Hydraulic Shadow Maps for the Pigeon Creek Flowage Dam Resettlement Admin 23 for Pigeon and Stanton Creeks, dated May 2, 2013, Cedar Corporation, Approved by the WI-DNR, June 24, 2013.
10. The Dam Hazard Assessment and the 100 year Hydraulic Shadow map for the Beaver Creek Dam on Beaver Creek, dated September of 2014, General Engineering Company, Approved by the WI-DNR, December 12, 2014.
11. The Dam Hazard Assessment and the 100 year Hydraulic Shadow map for the Trump Lake Dam on Trump Coulee Creek, dated September of 2014, General Engineering Company, Approved by the WI-DNR, December 12, 2014.
12. The Dam Hazard Assessment and the 100 year Hydraulic Shadow map for the Harold Ludeman Dam on Pine Creek, dated February of 2015, Ayres Associates, Approved by the WI-DNR, March 11, 2015.

These maps are incorporated into this chapter. The hydraulic shadow area shall be floodway for purposes of administering and enforcing of this chapter.

(3) ESTABLISHMENT OF DISTRICTS

The regional floodplain areas are divided into three districts as follows:

- (a) The Floodway District (FW) is the channel of a river or stream and those portions of the floodplain adjoining the channel required to carry the regional floodwaters.
- (b) The Floodfringe District (FF) is that portion of the floodplain between the regional flood limits and the floodway.
- (c) The General Floodplain District (GFP) is those areas that have been or may be covered by floodwater during the regional flood, and does not have a BFE or floodway boundary determined including A, AH, and AO zones on the FIRM.

(4) LOCATING FLOODPLAIN BOUNDARIES

Discrepancies between boundaries on the official floodplain zoning map and actual field conditions shall be resolved using the criteria in paragraphs (a) or (b) below. If a significant difference exists, the map shall be amended according to s. 20.36. The zoning administrator can rely on a boundary derived from a profile elevation to grant or deny a land use permit, whether or not a map amendment is required. The zoning administrator shall be responsible for documenting actual pre-development field conditions and the basis upon which the district boundary was determined and for initiating any map amendments required under this section. Disputes between the zoning administrator and an applicant over the district boundary line shall be settled according to s. 20.32(3) and the criteria in (a) and (b) below. Where the flood profiles are based on established base flood elevations from a FIRM, FEMA must approve any map amendment or revision pursuant to s. 20.36 amendments.

- (a) If flood profiles exist, the map scale and the profile elevations shall determine the district boundary. The regional or base flood elevations shall govern if there are any discrepancies.
- (b) Where flood profiles do not exist, the location of the boundary shall be determined by the map scale

(5) REMOVAL OF LANDS FROM FLOODPLAIN

Compliance with the provisions of this ordinance shall not be grounds for removing land from the floodplain unless it is filled at least two feet above the regional or base flood elevation, the fill is contiguous to land outside the floodplain, and the map is amended pursuant to s. 20.36.

**Note:** This procedure does not remove the requirements for the mandatory purchase of flood insurance. The property owner must contact FEMA to request a Letter of Map Change (LOMC).

(6) COMPLIANCE

Any development or use within the areas regulated by this ordinance shall be in compliance with the terms of this ordinance, and other applicable local, state, and federal regulations.

(7) MUNICIPALITIES AND STATE AGENCIES REGULATED

Unless specifically exempted by law, all cities, villages, towns, and counties are required to comply with this ordinance and obtain all necessary permits. State agencies are required to comply if s. 13.48(13), Stats. applies. The construction, reconstruction, maintenance and repair of state highways and bridges by the Wisconsin Department of Transportation are exempt when s. 30.2022 Stats. applies.

(8) ABROGATION AND GREATER RESTRICTIONS

- (a) This ordinance supersedes all the provisions of any municipal zoning ordinance enacted under ss. 59.69, 59.692 or 59.694 for counties; s. 62.23 for cities; or s. 61.35 for villages; or s. 87.30, Stats. which relate to floodplains. If another ordinance is more restrictive than this ordinance, that ordinance shall continue in full force and effect to the extent of the greater restrictions, but not otherwise.
- (b) This ordinance is not intended to repeal, abrogate or impair any existing deed restrictions, covenants or easements. If this ordinance imposes greater restrictions, the provisions of this ordinance shall prevail.

(9) INTERPRETATION

In their interpretation and application, the provisions of this ordinance are the minimum requirements liberally construed in favor of the governing body and are not a limitation on or repeal of any other powers granted by the Wisconsin Statutes. If a provision of this ordinance, required by ch. NR 116, Wis. Adm. Code, is unclear, the provision shall be interpreted in light of the standards in effect on the date of the adoption of this ordinance or in effect on the date of the most recent text amendment to this ordinance.

(10) WARNING AND DISCLAIMER OF LIABILITY

The flood protection standards in this ordinance are based on engineering experience and scientific research. Larger floods may occur or the flood height may be increased by man-made or natural causes. This ordinance does not imply or guarantee that non-floodplain areas or permitted floodplain uses will be free from flooding and flood damages. Nor does this ordinance create liability on the part of, or a cause of action against, the municipality or any officer or employee thereof for any flood damage that may result from reliance on this ordinance.

(11) SEVERABILITY

Should a court of competent jurisdiction declare any portion of this ordinance unconstitutional or invalid, the remainder of this ordinance shall not be affected.

**20.06 GENERAL STANDARDS APPLICABLE TO ALL FLOODPLAIN DISTRICTS**

The community shall review all permit applications to determine whether proposed building sites will be reasonably safe from flooding. If a proposed building site is in a flood-prone area, all new construction and substantial improvements shall be designed and anchored to prevent flotation, collapse, or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads; be constructed with flood resistant materials; be constructed to minimize flood damages and to ensure that utility and mechanical equipment is designed and/or located so as to prevent water from entering or accumulating within the equipment during conditions of flooding.

Subdivisions shall be reviewed for compliance with the above standards. All subdivision proposals (including manufactured parks) shall include regional flood elevation and floodway data for any development that meets the subdivision definition of this ordinance and all other requirements in Section 20.30 (2). Adequate drainage shall be provided to reduce exposure to flood hazards and all public utilities and facilities, such as sewer, gas, electrical, and water systems are located and constructed to minimize or eliminate flood damages.

**20.07 HYDRAULIC AND HYDROLOGIC ANALYSES**

- (1) No floodplain development shall:
  - (a) Obstruct flow, defined as development which blocks the conveyance of floodwater by itself or development, causing any increase in the regional flood height; or
  - (b) Cause any increase in the regional flood height due to the loss of floodplain storage area.
- (2) The Zoning Administrator shall deny permits if it is determined the proposed development will obstruct flow or cause any increase in the regional flood height based on the officially adopted FIRM or other adopted map, unless the provisions of s. 20.36 are met.

**20.08 WATERCOURSE ALTERATIONS**

No land use permit to alter or relocate a watercourse in a mapped floodplain shall be issued until the local official has notified in writing all adjacent municipalities, the Department and FEMA regional offices and required the applicant to secure all necessary state and federal permits. The flood carrying capacity of any altered or relocated watercourse shall be maintained and the standards of s 20.07 must be met.

As soon as is practicable, but not later than six months after the date of the watercourse alteration or relocation, the zoning administrator shall notify FEMA of the changes by submitting appropriate technical or scientific data in accordance with NFIP guidelines that shall be used to revise the FIRM, risk premium rates and floodplain management regulations as required.

**20.09 CHAPTER 30, 31, WIS. STATS. DEVELOPMENT**

Development that requires a permit from the Department, under chs. 30 and 31, Wis. Stats. such as docks, piers, wharves, bridges, culverts, dams and navigational aids, may be allowed if the necessary permits are obtained and amendments to the floodway lines, water surface profiles, BFE's established in the FIS, or other data from the officially adopted FIRM, or other floodplain zoning maps or the floodplain zoning ordinance are made according to s. 20.36.

**20.10 PUBLIC OR PRIVATE CAMPGROUNDS**

Public or private campgrounds shall have a low flood damage potential and shall meet the following provisions:

- (1) The campground is approved by the Department of Health Services.
- (2) A land use permit for the campground is issued by the zoning administrator.
- (3) The character of the river system and the elevation of the campground is such that a 72-hour warning of an impending flood can be given to all campground occupants.

FLOODPLAIN ZONING CODE 20.10(4)

- (4) There is an adequate flood warning procedure for the campground that offers the minimum notice required under this section to all persons in the campground. This procedure shall include a written agreement between the campground owner, the municipal emergency government coordinator and the chief law enforcement official which specifies the flood elevation at which evacuation shall occur, personnel responsible for monitoring flood elevations, types of warning systems to be used and the procedures for notifying at-risk parties, and the methods and personnel responsible for conducting the evacuation.
- (5) This agreement shall be for no more than one calendar year, at which time the agreement shall be reviewed and updated - by the officials identified in sub. (4) - to remain in compliance with all applicable regulations, including those of the state department of health services and all other applicable regulations.
- (6) Only camping units that are fully licensed, if required, and ready for highway use are allowed.
- (7) The camping units may not occupy any site in the campground for more than 180 consecutive days, at which time the camping unit must be removed from the floodplain for a minimum of 24 hours.
- (8) All camping units that remain on site for more than 30 days shall be issued a limited authorization by the campground operator, a written copy of which is kept on file at the campground. Such authorization shall allow placement of a camping unit for a period not to exceed 180 days and shall ensure compliance with all the provisions of this section.
- (9) The municipality shall monitor the limited authorizations issued by the campground operator to assure compliance with the terms of this section.
- (10) All structures that do not meet the definition of a camping unit or mobile recreational vehicle, or that remain in place for more than 180 consecutive days, must meet the applicable requirements in either s. 20.11 or s. 20.16 for the floodplain district in which the structure is located.
- (11) The campground shall have signs clearly posted at all entrances warning of the flood hazard and the procedures for evacuation when a flood warning is issued.
- (12) All service facilities, including but not limited to refuse collection, electrical service, natural gas lines, propane tanks, sewage systems and wells shall be properly anchored and placed at or flood proofed to the flood protection elevation.

**20.11 FLOODWAY DISTRICT (FW)**

**20.12 APPLICABILITY**

This section applies to all floodway areas on the floodplain zoning maps and those identified pursuant to s.20.24.

**20.13 PERMITTED USES**

The following open space uses are allowed in the floodway district and the floodway areas of the general floodplain district, if

- they are not prohibited by any other ordinance;
  - they meet the standards in s. 20.14 and 20.15; and
  - all permits or certificates have been issued according to s. 20.30:
- (1) Agricultural uses, such as: farming, outdoor plant nurseries, horticulture, viticulture and wild crop harvesting.
  - (2) Nonstructural industrial and commercial uses, such as loading areas, parking areas and airport landing strips.
  - (3) Nonstructural recreational uses, such as golf courses, tennis courts, archery ranges, picnic grounds, boat ramps, swimming areas, parks, wildlife and nature preserves, game farms, fish hatcheries, shooting, trap and skeet activities, hunting and fishing areas and hiking and horseback riding trails, subject to the fill limitations of s. 20.14 (4).
  - (4) Uses or structures accessory to open space uses, or classified as historic structures that comply with ss. 20.14 and 20.15.
  - (5) Extraction of sand, gravel or other materials that comply with s. 20.14 (4).
  - (6) Functionally water-dependent uses, such as docks, piers or wharves, dams, flowage areas, culverts, navigational aids and river crossings of transmission lines, and pipelines that comply with chs. 30, 31, Stats.
  - (7) Public utilities, streets and bridges that comply with s. 20.14 (3).

**20.14 STANDARDS FOR DEVELOPMENTS IN FLOODWAY AREAS**

(1) GENERAL

- (a) Any development in floodway areas shall comply with s. 20.06 and have a low flood damage potential.
- (b) Applicants shall provide the following data to determine the effects of the proposal according to s. 20.07 and s. 20.30 (2) (c):
  - 1. A cross-section elevation view of the proposal, perpendicular to the watercourse, showing if the proposed development will obstruct flow; or
  - 2. An analysis calculating the effects of this proposal on regional flood height.
- (c) The Zoning Administrator shall deny the permit application if the project will cause any increase in the flood elevations upstream or downstream, based on the data submitted for subd. (b) above.

(2) STRUCTURES. Structures accessory to permanent open space uses or functionally dependent on a waterfront location may be allowed by permit if the structures comply with the following criteria:

- (a) Not designed for human habitation, does not have a high flood damage potential and is constructed to minimize flood damage;
- (b) Shall have a minimum of two openings on different walls having a total net area not less than one square inch for every square foot of enclosed area, and the bottom of all such openings being no higher than one foot above grade. The openings shall be equipped with screens, louvers, or other coverings or devices provided that they permit the automatic entry and exit of floodwater;
- (c) Must be anchored to resist flotation, collapse and lateral movement;
- (d) Mechanical and utility equipment must be elevated or flood protected to or above the flood protection elevation; and
- (e) It must not obstruct flow of floodwaters or cause any increase in flood levels during the occurrence of a regional flood.

- (3) Public utilities, streets and bridges may be allowed by permit, if:
  - (a) Adequate flood proofing measures are provided to the flood protection elevation; and
  - (b) Construction meets the development standards of s. 20.07.
- (4) Fills or deposition of materials may be allowed by permit, if:
  - (a) The requirements of s. 20.07 are met;
  - (b) No material is deposited in the navigable channel unless a permit is issued by the Department pursuant to ch. 30, Stats. and a permit pursuant to s. 404 of the Federal Water Pollution Control Act, Amendments of 1972, 33 U.S.C. 1344 has been issued, if applicable, and the other requirements of this section are met;
  - (c) The fill or other materials will be protected against erosion by riprap, vegetative cover, sheet piling or bulkheading; and
  - (d) The fill is not classified as a solid or hazardous waste material

**20.15 PROHIBITED USES**

All uses not listed as permitted uses in s. 20.13 are prohibited, including the following uses:

- (1) Habitable structures, structures with high flood damage potential, or those not associated with permanent open-space uses;
- (2) Storing materials that are buoyant, flammable, explosive, injurious to property, water quality, or human, animal, plant, fish or other aquatic life;
- (3) Uses not in harmony with or detrimental to uses permitted in the adjoining districts;

- (4) Any private or public sewage systems, except portable latrines that are removed prior to flooding and systems associated with recreational areas and Department-approved campgrounds that meet the applicable provisions of local ordinances and Ch. SPS 383, Wis. Adm. Code.
- (5) Any public or private wells, which are used to obtain potable water, except those for recreational areas that meet the requirements of local ordinances and chs. NR 811 and NR 812, Wis. Adm. Code;
- (6) Any solid or hazardous waste disposal sites;
- (7) Any wastewater treatment ponds or facilities, except those permitted under s. NR 110.15(3)(b), Wis. Adm. Code;
- (8) Any sanitary sewer or water supply lines except those to service existing or proposed development located outside the floodway, which complies with the regulations for the floodplain area occupied.

**20.16 FLOODFRINGE DISTRICT (FF)**

**20.17 APPLICABILITY**

This section applies to all floodfringe areas shown on the floodplain zoning maps and those identified pursuant to s.20.24.

**20.18 PERMITTED USES**

Any structure, land use, or development is allowed in the floodfringe district if the standards in s. 20.07 are met, the use is not prohibited by this or any other ordinance or regulation and all permits or certificates specified in s. 20.30 have been issued.

**20.19 STANDARDS FOR DEVELOPMENT IN FLOODFRINGE AREAS**

- (1) All provisions of Section 20.07 shall apply in addition to the following requirements according to the use requested. Any existing structure in the floodfringe must meet the requirements of Section 20.25, Non-conforming Uses;
- (2) **RESIDENTIAL USES.** Any structure, including a manufactured home, which is to be newly constructed or moved into the floodfringe, shall meet or exceed the following standards. Any existing structure in the floodfringe must meet the requirements of Section 20.25, Non-Conforming Uses;
  - (a) The elevation of the lowest floor shall be at or above the flood protection elevation on fill unless the requirements of s. 20.19 (1) (b) can be met. The fill shall be one foot or more above the regional flood elevation extending at least 15 feet beyond the limits of the structure;
  - (b) The basement or crawlway floor may be placed at the regional flood elevation if it is dry flood proofed to the flood protection elevation. No basement or crawlway floor is allowed below the regional flood elevation;
  - (c) Contiguous dry land access shall be provided from a structure to land outside of the floodplain, except as provided in subd. (d);
  - (d) In developments where existing street or sewer line elevations make compliance with subd. (c) impractical, the municipality may permit new development and substantial improvements where roads are below the regional flood elevation, if;
    1. The municipality has written assurance from police, fire and emergency services that rescue and relief will be provided to the structure(s) by wheeled vehicles during a regional flood event; or
    2. The municipality has a DNR-approved emergency evacuation plan.
- (3) **ACCESSORY STRUCTURES OR USES.** Accessory structures shall be constructed on fill with the lowest floor at or above the regional flood elevation.

FLOODPLAIN ZONING CODE 20.19(4)

- (4) **COMMERCIAL USES:** Any commercial structure that is erected, altered or moved into the floodfringe area shall meet the requirements of s. 20.19 (2). Subject to the requirements of sub. (6), storage yards, surface parking lots and other such uses may be placed at lower elevations if an adequate warning system exists to protect life and property.
- (5) **MANUFACTURING AND INDUSTRIAL USES:** Any manufacturing or industrial structure which is erected, altered or moved into the floodfringe area shall be protected to the flood protection elevation using fill, levees, floodwalls, or other flood proofing measures in s. 20.34. Subject to the requirements of sub. (6), storage yards, surface parking lots and other such uses may be placed at lower elevations if an adequate warning system exists to protect life and property.
- (6) **STORAGE OF MATERIALS:** Materials that are buoyant, flammable, explosive, or injurious to property, water quality or human, animal, plant, fish or aquatic life shall be stored at or above the flood protection elevation or flood proofed in compliance with s. 20.34. Adequate measures shall be taken to ensure that such materials will not enter the water body during flooding.
- (7) **PUBLIC UTILITIES, STREETS AND BRIDGES:** All utilities, streets and bridges shall be designed to be compatible with comprehensive floodplain development plans; and
  - (a) When failure of public utilities, streets and bridges would endanger public health or safety, or where such facilities are deemed essential, construction of and substantial improvements to such facilities may only be permitted if they are flood proofed in compliance with s. 20.34 to the flood protection elevation;
  - (b) Minor roads or nonessential utilities may be constructed at lower elevations if they are designed to withstand flood forces to the regional flood elevation.
- (8) **SEWAGE SYSTEMS.** All onsite sewage disposal systems shall be designed to minimize or eliminate infiltration of flood water into the system pursuant to s. 20.34, to the flood protection elevation and meet the provisions of all local ordinances and Ch. SPS 383, Wis. Adm. Code

FLOODPLAIN ZONING CODE 20.19(9)

- (9) **WELLS:** All wells shall be flood proofed, pursuant to s. 20.34, to the flood protection elevation and shall meet the provisions of chs. NR 811 and NR 812, Wis. Adm. Code.
- (10) **SOLID WASTE DISPOSAL SITES:** Disposal of solid or hazardous waste is prohibited in floodfringe areas.
- (11) **DEPOSITION OF MATERIALS:** Any deposited material must meet all the provisions of this ordinance.
- (12) **MANUFACTURED HOMES**
  - (a) Owners or operators of all manufactured home parks and subdivisions shall provide adequate surface drainage to minimize flood damage, and prepare, secure approval and file an evacuation plan, indicating vehicular access and escape routes, with local emergency management authorities.
  - (b) In existing manufactured home parks, all new homes, replacement homes on existing pads, and substantially improved homes shall:
    - 1. have the lowest floor elevated to the flood protection elevation; and
    - 2. be anchored so they do not float, collapse or move laterally during a flood.
  - (c) Outside of existing manufactured home parks, including new manufactured home parks and all single units outside of existing parks, all new, replacement and substantially improved manufactured homes shall meet the residential development standards for the floodfringe in s. 20.19 (2).
- (13) **MOBILE RECREATIONAL VEHICLES**

All mobile recreational vehicles that are on site for 180 consecutive days or more or are not fully licensed and ready for highway use shall meet the elevation and anchoring requirements in s. 20.19 (12) (b) and (c). A mobile recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick-disconnect utilities and security devices and has no permanently attached additions.

**20.20 GENERAL FLOODPLAIN DISTRICT (GFP)**

**20.21 APPLICABILITY**

The provisions for this district shall apply to all floodplains for which flood profiles are not available or where flood profiles are available but floodways have not been delineated. Floodway and floodfringe districts shall be delineated when adequate data is available.

**20.22 PERMITTED USES**

Pursuant to s. 20.24, it shall be determined whether the proposed use is located within a floodway or floodfringe area.

Those uses permitted in floodway (s. 20.13) and floodfringe areas (s. 20.18) are allowed within the general floodplain district, according to the standards of s. 20.23, provided that all permits or certificates required under s. 20.30 have been issued.

**20.23 STANDARDS FOR DEVELOPMENT IN THE GENERAL FLOODPLAIN DISTRICT**

S. 20.11 applies to floodway areas; s. 20.16 applies to floodfringe areas. The rest of this ordinance applies to either district.

- (1) In AO/AH zones, the structures lowest floor must meet one of the conditions listed below, whichever is higher:
  - (a) At or above the flood protection elevation; or
  - (b) Two (2) feet above the highest adjacent grade around the structure; or
  - (c) The depth as shown on the FIRM.
- (2) In AO/AH zones, provide plans showing adequate drainage paths to guide floodwaters around structure.

**20.24 DETERMINING FLOODWAY AND FLOODFRINGE LIMITS**

Upon receiving an application for development within the general floodplain district, the zoning administrator shall:

- (1) Require the applicant to submit two copies of an aerial photograph or a plan which shows the proposed development with respect to the general floodplain district limits, stream channel, and existing floodplain developments, along with a legal description of the property, fill limits and elevations, building floor elevations and flood proofing measures and the flood zone as shown on the FIRM.
- (2) Require the applicant to furnish any of the following information deemed necessary by the Department to evaluate the effects of the proposal upon flood height and flood flows, regional flood elevation and to determine floodway boundaries:
  - (a) A Hydrologic and Hydraulic Study as specified in s. 20.32 (2) (c).
  - (b) Plan (surface view) showing elevations or contours of the ground; pertinent structure, fill or storage elevations; size, location and layout of all proposed and existing structures on the site; location and elevations of streets, water supply, and sanitary facilities; soil types and other pertinent information;
  - (c) Specifications for building construction and materials, flood proofing, filling, dredging, channel improvement, storage, water supply and sanitary facilities.

**20.25 NONCONFORMING USES**

**20.26 GENERAL**

- (1) **APPLICABILITY**  
If these standards conform to s. 59.69(10), Stats. for counties or s. 62.23(7)(h), Stats., for cities and villages, they shall apply to all modifications or additions to any nonconforming use or structure and to the use of any structure or premises which was lawful before the passage of this ordinance or any amendment thereto.

(2) The existing lawful use of a structure or its accessory use, which is not in conformity with the provisions of this ordinance, may continue subject to the following conditions:

(a) No modifications or additions to a nonconforming use or structure shall be permitted unless they comply with this ordinance. The words “modification” and “addition” include, but are not limited to, any alteration, addition, modification, structural repair, rebuilding or replacement of any such existing use, structure or accessory structure or use. Maintenance is not considered a modification; this includes painting, decorating, paneling, and other nonstructural components and the maintenance, repair, or replacement of existing private sewage or water supply systems or connections to public utilities. Any costs associated with the repair of a damaged structure are not considered maintenance.

The construction of a deck that does not exceed 200 square feet and that is adjacent to the exterior wall of a principal structure is not an extension, modification or addition. The roof of the structure may extend over a portion of the deck in order to provide safe ingress and egress to the principal structure.

(b) If a nonconforming use or the use of a nonconforming structure is discontinued for 12 consecutive months, it is no longer permitted and any future use of the property, and any structure or building thereon, shall conform to the applicable requirements of this ordinance;

(c) The municipality shall keep a record which lists all nonconforming uses and Nonconforming structures, their present equalized assessed value, the cost of all modifications or additions that have been permitted, and the percentage of the structure's total current value those modifications represent;

FLOODPLAIN ZONING CODE 20.26(2)(d)

- (d) No modification or addition to any nonconforming structure or any structure with a nonconforming use, which over the life of the structure would equal or exceed 50% of its present equalized assessed value, shall be allowed unless the entire structure is permanently changed to a conforming structure with a conforming use in compliance with the applicable requirements of this ordinance. Contiguous dry land access must be provided for residential and commercial uses in compliance with s. 20.19 (2). The costs of elevating the lowest floor of a nonconforming building or a building with a nonconforming use to the flood protection elevation are excluded from the 50% provisions of this paragraph.
- (e) No maintenance to any nonconforming structure or any structure with a nonconforming use, the cost of which would equal or exceed 50% of its present equalized assessed value, shall be allowed unless the entire structure is permanently changed to a conforming structure with a conforming use in compliance with the applicable requirements of this ordinance. Contiguous dry land access must be provided for residential and commercial uses in compliance with s. 20.19 (2);
- (f) If on a per event basis the total value of the work being done under (d) and (e) equals or exceeds 50% of the present equalized assessed value, the work shall not be permitted unless the entire structure is permanently changed to a conforming structure with a conforming use in compliance with the applicable requirements of this ordinance. Contiguous dry land access must be provided for residential and commercial uses in compliance with s. 20.19 (2);
- (g) Except as provided in subd. (h), if any nonconforming structure or any structure with a nonconforming use is destroyed or is substantially damaged, it cannot be replaced, reconstructed or rebuilt unless the use and the structure meet the current ordinance requirements. A structure is considered substantially damaged if the total cost to restore the structure to its pre-damaged condition equals or exceeds 50% of the structures present equalized assessed value.

- (h) For nonconforming buildings that are substantially damaged or destroyed by a non-flood disaster, the repair or reconstruction of any such nonconforming building shall be permitted in order to restore it to the size and use in effect prior to the damage event, provided that the minimum federal code requirements below are met and all required permits have been granted prior to the start of construction:
1. Residential Structures.
    - a. Shall have the lowest floor, including basement, elevated to or above the base flood elevation using fill, pilings, columns, posts or perimeter walls. Perimeter walls must meet the requirements of s. 20.34.
    - b. Shall be anchored to prevent flotation, collapse, or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoying and shall be constructed with methods and materials resistant to flood damage.
    - c. Shall be constructed with electrical, heating, ventilation, plumbing and air conditioning equipment and other facilities that are designed and/or elevated so as to prevent water from entering or accumulating within the components during flooding conditions.
    - d. In A zones, obtain, review and utilize any flood data available from a federal, state or other source.
    - e. In AO zones with no elevation specified, shall have the lowest floor, including basements, meet the standards in section 20.23 (1).
    - f. In AO zones, shall have adequate drainage paths around structures on slopes to guide floodwaters around and away from the structure.
  2. Non-Residential Structures.
    - a. Shall meet the requirements of section 20.26 (2) (a-g).
    - b. Shall either have the lowest floor, including basement, elevated to or above the regional flood elevation; or together with attendant utility and sanitary facilities, shall meet the standards in section 20.34 (1) and (2).
    - c. In AO zones, with no elevation specified, shall have the lowest floor, including basement, meet the standards in section 20.23 (1).

- (i) A nonconforming historic structure may be altered if the alteration will not preclude the structures continued designation as a historic structure, the alteration will comply with section 20.14 (1), flood resistant materials are used, and construction practices and floodproofing methods that comply with section 20.34 are used. Repair or rehabilitation of historic structures shall be exempt from the development standards of section n20.26 (2) (h) 1. If it is determined that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and is the minimum necessary to preserve the historic character and design of the structure.

**20.27 FLOODWAY AREAS**

- (1) No modification or addition shall be allowed to any nonconforming structure or any structure with a nonconforming use in a floodway area, unless such modification or addition:
  - (a) Has been granted a permit or variance, which meets all ordinance requirements;
  - (b) Meets the requirements of s. 20.26;
  - (c) Will not increase the obstruction to flood flows or regional flood height; and
  - (d) Any addition to the existing structure shall be flood proofed, pursuant to s. 20.34,
  - (e) If any part of the foundation below the flood protection elevation is enclosed, the following standards shall apply:
    - 1. The enclosed area shall be designed by a registered architect or engineer to allow for the efficient entry and exit of flood waters without human intervention. A minimum of two openings must be provided with a minimum net area of at least one square inch for every one square foot of the enclosed area. The lowest part of the opening can be no more than 12 inches above the adjacent grade;
    - 2. The parts of the foundation located below the flood protection elevation must be constructed of flood resistant materials;
    - 3. Mechanical and utility equipment must be elevated or flood proofed to or above the flood protection elevation and;
    - 4. The use must be limited to parking, building access, or limited storage.

- (2) No new on-site sewage disposal system, or addition to an existing on-site sewage disposal system, except where an addition has been ordered by a government agency to correct a hazard to public health, shall be allowed in a floodway area. Any replacement, repair or maintenance of an existing onsite sewage disposal system in a floodway area shall meet the applicable requirements of all municipal ordinances, section 20.34 (2) and Ch. SPS 383, Wis. Adm. Code.
- (3) No new well or modification to an existing well used to obtain potable water shall be allowed in a floodway area. Any replacement, repair or maintenance of an existing well in a floodway area shall meet the applicable requirements of all municipal ordinances and chs. NR 811 and NR 812, Wis. Adm. Code.

**20.28 FLOODFRINGE AREAS**

- (1) No modification or addition shall be allowed to any nonconforming structure or any structure with a nonconforming use unless such modification or addition has been granted a permit or variance by the municipality, and the modification or addition shall be placed on fill or flood proofed to the flood protection elevation in compliance with the standards for that particular use in s. 20.19, except where s. 20.28 (2) is applicable.
- (2) Where compliance with the provisions of par. (1) would result in unnecessary hardship and only where the structure will not be used for human habitation or be associated with a high flood damage potential, the Board of Adjustment/Appeals, using the procedures established in s. 20.32, may grant a variance from those provisions of par. (1) for modifications or additions, using the criteria listed below. Modifications or additions that are protected to elevations lower than the flood protection elevation may be permitted if:
  - (a) No floor is allowed below the regional flood elevation for residential or commercial structures;
  - (b) Human lives are not endangered;
  - (c) Public facilities, such as water or sewer, will not be installed;
  - (d) Flood depths will not exceed two feet;
  - (e) Flood velocities will not exceed two feet per second; and
  - (f) The structure will not be used for storage of materials as described in s. 20.19 (6).

- (3) All new private sewage disposal systems, or addition to, replacement, repair or maintenance of a private sewage disposal system shall meet all the applicable provisions of all local ordinances, s. 20.34 (3) and ch. SPS 383, Wis. Adm. Code.
- (4) All new wells, or addition to, replacement, repair or maintenance of a well shall meet the applicable provisions of this ordinance s. 20.34 (3) and ch. NR 811 and NR 812, Wis. Adm. Code.

**20.29 ADMINISTRATION**

Where a zoning administrator, planning agency or a board of adjustment/appeals has already been appointed to administer a zoning ordinance adopted under ss. 59.69, 59.692 or 62.23(7), Stats. these officials shall also administer this ordinance.

**20.30 ZONING ADMINISTRATOR**

- (1) The zoning administrator is authorized to administer this ordinance and shall have the following duties and powers:
  - (a) Advise applicants of the ordinance provisions, assist in preparing permit applications and appeals, and assure that the regional flood elevation for the proposed development is shown on all permit applications.
  - (b) Issue permits and inspects properties for compliance with provisions of this ordinance and issue certificates of compliance where appropriate.
  - (c) Inspect and assess all damaged floodplain structures to determine if substantial damage to the structure has occurred.

FLOODPLAIN ZONING CODE 20.30(1)(d)

- (d) Keep records of all official actions such as:
  - 1. All permits issued, inspections made, and work approved;
  - 2. Documentation of certified lowest floor and regional flood elevations;
  - 3. Floodproofing certificates;
  - 4. Water surface profiles, floodplain zoning maps and ordinances, nonconforming uses and structures including changes, appeals, variances and amendments;
  - 5. All substantial damage assessment reports for floodplain structures;
  - 6. List of nonconforming structures and uses.
  
- (e) Submit copies of the following items to the Department Regional office:
  - 1. Within 10 days of the decision, a copy of any decisions on variances, appeals for map or text interpretations, and map or text amendments;
  
  - 2. Copies of any case-by-case analyses, and any other information required by the Department including an annual summary of the number and types of floodplain zoning actions taken.
  
  - 3. Copies of substantial damage assessments performed and all related correspondence concerning the assessments
  
- (f) Investigate, prepare reports, and report violations of this ordinance to the municipal zoning agency and attorney for prosecution. Copies of the reports shall also be sent to the Department Regional office.
  
- (g) It shall be unlawful to construct or use any structure, land or water in violation of any of the provisions of this chapter. In case of any violation, the County Board, Zoning Administrator, Zoning Committee or any property owner who would be specifically damaged by such violation may institute appropriate action or proceeding to enjoin a violation of this chapter.

(h) The Jackson County Zoning Administrator is authorized to post an order stopping work upon land, which has had a permit revoked or on land currently undergoing activity in violation of this ordinance. Notice is given by both posting upon the land where the violation occurs with a stop work placard and by mailing a copy of the order by certified mail to the person whose activity is in violation of this ordinance. The order shall specify that the activity must cease or be brought into compliance immediately.

(i) Submit copies of text and map amendments to the FEMA Regional office.

(2) LAND USE PERMIT

A land use permit shall be obtained before any new development or any repair or change in the use of a building or structure, including sewer and water facilities, may be initiated. Application to the zoning administrator shall include:

(a) GENERAL INFORMATION

1. Name and address of the applicant, property owner and contractor;
2. Legal description, proposed use, and whether it is new construction or a modification;

(b) SITE DEVELOPMENT PLAN

A site plan drawn to scale shall be submitted with the permit application form and shall contain:

1. Location, dimensions, area and elevation of the lot;
2. Location of the ordinary high water mark of any abutting navigable waterways;
3. Location of any structures with distances measured from the lot lines and street centerlines;
4. Location of any existing or proposed on-site sewage systems or private water supply systems;
5. Location and elevation of existing or future access roads;
6. Location of floodplain and floodway limits as determined from the official floodplain zoning maps;
7. The elevation of the lowest floor of the proposed building(s) and any fill using the vertical datum from the adopted study, either National Geodetic Vertical Datum (NGVD) or North American Vertical Datum (NAVD).
8. Data sufficient to determine the regional flood elevation in NGVD or NAVD at the location of the development and to determine whether or not the requirements of s. 20.11 or 20.16 are met; and
9. Data to determine if the proposed development will cause an obstruction to flow or an increase in regional flood height or discharge according to s. 20.07. This may include any of the information noted in s. 20.14 (1).

(c) HYDRAULIC AND HYDROLOGIC STUDIES TO ANALYZE DEVELOPMENT

All hydraulic and hydrologic studies shall be completed under the direct supervision of a professional engineer registered in the state. The study contractor shall be responsible for the technical adequacy of the study. All studies shall be reviewed and approved by the Department.

1. Zone A Floodplains:

a. Hydrology

- i. The appropriate method shall be based on the standards in ch. NR116.07 (3), Wis. Adm. Code, Hydrologic Analysis; Determination of Regional Flood Discharge.

b. Hydraulic Modeling

The regional flood elevation shall be based on the standards in ch. NR116.07 (4), Wis. Adm. Code, Hydraulic Analysis; Determination of Regional Flood Elevation and the following:

- i. Determination of the required limits of the hydraulic model shall be based on detailed study information for downstream structures (dam, bridge, culvert) to determine adequate starting WSEL for the study.
- ii. Channel sections must be surveyed.
- iii. Minimum four foot contour data in the overbanks shall be used for the development of cross-section overbank and floodplain mapping.
- iv. A maximum distance of 500 feet between cross-sections is allowed in developed areas with additional intermediate cross-sections required at transitions in channel bottom slope including a survey of the channel at each location.

FLOODPLAIN ZONING CODE 20.30(2)(c)(1)(b)(v)

- v. The most current version of HEC-RAS shall be used.
- vi. A survey of bridge and culvert openings and the top of road is required at each structure.
- vii. Additional cross-sections are required at the downstream and upstream limits of the proposed development and any necessary intermediate locations based on the length of the reach, if greater than 500 feet.
- viii. Standard accepted engineering practices shall be used when assigning parameters for the base model such as flow, Mannings N values, expansion and contraction coefficients or effective flow limits. The base model shall be calibrated to past flooding data such as high water marks to determine the reasonableness of the model results. If no historical data is available, adequate justification shall be provided for any parameter outside standard accepted engineering practices.
- ix. The model must extend past the upstream limit of the difference in the existing and proposed flood profiles in order to provide a tie-in to existing studies. The height difference between the proposed flood profile and the existing study profiles shall be no more than 0.00 feet.

c. Mapping

A work map of the reach studied shall be provided showing all cross section locations, floodway/floodplain limits based on the best available topographic data, geographic limits of the proposed development and whether the proposed development is located in the floodway:

- i. If the proposed development is located outside of the floodway, then it is determined to have no impact on the regional flood elevation.
- ii. If any part of the proposed development is in the floodway, it must be added to the base model to show the difference between existing and proposed conditions. The study must ensure that all coefficients remain the same as in the existing model, unless adequate justification based on standard accepted engineering practices is provided.

2. Zone AE Floodplains:
  - a. Hydrology

If the proposed hydrology will change the existing study, the appropriate method to be used shall be based on ch. NR 116.07 (3) Wis. Adm. Code, Hydrology Analysis; Determination of Regional Flood Discharge
  - b. Hydraulic Model

The regional flood elevation shall be based on the standards in ch. NR116.07 (4) Wis. Adm. Code, Hydraulic Analysis; Determination of Regional Flood Elevation and the following:
    - i. Duplicate effective model. The effective model shall be reproduced to ensure correct transference of the model data and to allow integration of the revised data to provide a continuous FIS model upstream and downstream of the revised reach. If data from the effective model is available, models shall be generated that duplicate the FIS profiles and the elevations shown in the Floodway Data Table in the FIS report to within 0.1 foot.
    - ii. Corrected Effective Model. The corrected effective model shall not include any man-made physical changes since the effective model data, but shall import the model into the most current version of HER-RAS for department review.
    - iii. Existing (Pre-Project Condition) Model. The existing model shall be required to support conclusions about the actual impacts of the project associated with the revised (Post-Project) model or to establish more up-to-date models on which to base the Revised (Post-Project) Model.
    - iv. Revised (Post-Project Condition) Model. The revised (Post-Project Condition) Model shall incorporate the existing model and any proposed changes to the topography caused by the proposed development. This model shall reflect proposed conditions.

FLOODPLAIN ZONING CODE 20.30(2)(c)(2)(b)(v)

- v. All changes to the Duplicate Effective Model and subsequent models must be supported by certified topographic information, bridge plans, construction plans and survey notes.
  - vi. Changes to the hydraulic models shall be limited to the stream reach for which the revision is being requested. Cross-sections upstream and downstream of the revised reach shall be identical to those in the effective model and result in water surface elevations and top widths computed by the revised models matching those in the effective models upstream and downstream of the revised reach as required. The Effective Model shall not be truncated.
- c. Mapping
- Maps and associated engineering data shall be submitted to the Department for review, which meet the following conditions:
- i. Consistency between the revised hydraulic models, the revised floodplain and floodway delineations, the revised flood profiles, topographic work map, annotated FIRMS and/or Flood Boundary Floodway Maps (FBFMs), construction plans, bridge plans.
  - ii. Certified topographic map of suitable scale, contour interval, and a planimetric map showing the applicable items. If a digital version of the map is available, it may be submitted in order that the FIRM may be more easily revised.
  - iii. Annotated FIRM panel showing the revised 1% and 0.2% annual chance floodplains and floodway boundaries.
  - iv. If an annotated FIRM and/or FBFM and digital mapping data (GIS or CADD) are used then all supporting documentation or metadata must be included with the data submission along with the Universal Transverse Mercator (UTM) projection and State Plane Coordinate System in accordance with FEMA mapping specifications.

FLOODPLAIN ZONING CODE 20.30(2)(c)(2)(c)(v)

- v. The revised floodplain boundaries shall tie into the effective floodplain boundaries.
- vi. All cross-sections from the effective model shall be labeled in accordance with the effective map and a cross-section look-up table shall be included to relate to the model input numbering scheme.
- vii. Both the current and proposed floodways shall be shown on the map.
- viii. The stream centerline, or profile baseline used to measure stream distances in the model shall be visible on the map.

(d) EXPIRATION

All permits issued under the authority of this ordinance shall expire 180 days after issuance.

(3) CERTIFICATE OF COMPLIANCE

No land shall be occupied or used, and no building which is hereafter constructed, altered, added to, modified, repaired, rebuilt or replaced shall be occupied until a certificate of compliance is issued by the zoning administrator, except where no permit is required, subject to the following provisions:

- (a) The certificate of compliance shall show that the building or premises or part thereof, and the proposed use, conform to the provisions of this ordinance;
- (b) Application for such certificate shall be concurrent with the application for a permit;
- (c) If all ordinance provisions are met, the certificate of compliance shall be issued within 10 days after written notification that the permitted work is completed
- (d) The applicant shall submit a certification signed by a registered professional engineer or registered land surveyor that the fill, lowest floor and flood proofing elevations are in compliance with the permit issued. Flood proofing measures also require certification by a registered professional engineer or registered architect that flood proofing measures meet the requirements of s. 20.34.

(4) OTHER PERMITS

Prior to obtaining a floodplain development permit, the applicant must secure all necessary permits from federal, state, and local agencies, including those required by the U.S. Army Corps of Engineers under s. 404 of the Federal Water Pollution Control Act, Amendments of 1972, 33 U.S.C. 1344.

**20.31 ZONING AGENCY**

(1) The Jackson County Zoning and Land Information Committee shall:

- (a) oversee the functions of the office of the zoning administrator; and
- (b) review and advise the Governing body on all proposed amendments to this ordinance, maps and text.

(2) This zoning agency shall not

- (a) grant variances to the terms of the ordinance in place of action by the Board of Adjustment/Appeals; or
- (b) amend the text or zoning maps in place of official action by the Governing body.

**20.32 BOARD OF ADJUSTMENT/APPEALS**

The Board of Adjustment/Appeals, created under s. 59.694, Stats. for counties or s. 62.23 (7) (e), Stats., for cities or villages, is hereby authorized or shall be appointed to act for the purposes of this ordinance. The Board shall exercise the powers conferred by Wisconsin Statutes and adopt rules for the conduct of business. The zoning administrator may not be the secretary of the Board.

(1) Powers and Duties: The Board of Adjustment/Appeals shall:

- (a) Appeals - Hear and decide appeals where it is alleged there is an error in any order, requirement, decision or determination made by an administrative official in the enforcement or administration of this ordinance.
- (b) Boundary Disputes - Hear and decide disputes concerning the district boundaries shown on the official floodplain zoning map.
- (c) Variances - Hear and decide, upon appeal, variances from the ordinance standards.

(2) APPEALS TO THE BOARD

- (a) Appeals to the board may be taken by any person aggrieved, or by any officer or department of the municipality affected by any decision of the zoning administrator or other administrative officer. Such appeal shall be taken within 30 days unless otherwise provided by the rules of the board, by filing with the official whose decision is in question, and with the board, a notice of appeal specifying the reasons for the appeal. The official whose decision is in question shall transmit to the board all records regarding the matter appealed.

(b) NOTICE AND HEARING FOR APPEALS INCLUDING VARIANCES

1. Notice - the board shall:
  - a. Fix a reasonable time for the hearing;
  - b. Publish adequate notice pursuant to Wisconsin Statutes, specifying the date, time, place and subject of the hearing;
  - c. Assure that notice shall be mailed to the parties in interest and the Department Regional office at least 10 days in advance of the hearing.
2. Hearing - any party may appear in person or by agent or attorney. The board shall:
  - a. Resolve boundary disputes according to s. 20.32 (3).
  - b. Decide variance applications according to s. 20.32 (4).
  - c. Decide appeals of permit denials according to s. 20.33.

(c) DECISION: The final decision regarding the appeal or variance application shall:

1. Be made within a reasonable time;
2. Be sent to the Department Regional office within 10 days of the decision
3. Be a written determination signed by the chairman or secretary of the Board;
4. State the specific facts that are the basis for the Board's decision
5. Either affirm, reverse, vary or modify the order, requirement, decision or determination appealed, in whole or in part, dismiss the appeal for lack of jurisdiction or grant or deny the variance application;
6. Include the reasons for granting an appeal, describing the hardship demonstrated by the applicant in the case of a variance, clearly stated in the recorded minutes of the Board proceedings.

(3) BOUNDARY DISPUTES

The following procedure shall be used by the Board in hearing disputes concerning floodplain district boundaries:

- (a) If a floodplain district boundary is established by approximate or detailed floodplain studies, the flood elevations or profiles shall prevail in locating the boundary. If none exist, other evidence may be examined.
- (b) In all cases, the person contesting the boundary location shall be given a reasonable opportunity to present arguments and technical evidence to the Board.
- (c) If the boundary is incorrectly mapped, the Board should inform the zoning committee or the person contesting the boundary location to petition the governing body for a map amendment according to s. 20.36.

(4) VARIANCE

- (a) The Board may, upon appeal, grant a variance from the standards of this ordinance if an applicant convincingly demonstrates that:
  - 1. Literal enforcement of the ordinance provisions will cause unnecessary hardship;
  - 2. The hardship is due to adoption of the floodplain ordinance and unique property conditions, not common to adjacent lots or premises. In such case the ordinance or map must be amended;
  - 3. The variance is not contrary to the public interest; and
  - 4. The variance is consistent with the purpose of this ordinance in s. 20.03.

- (b) In addition to the criteria in par. (a), to qualify for a variance under FEMA regulations, the following criteria must be met:
1. The variance may not cause any increase in the regional flood elevation;
  2. Variances can only be granted for lots that are less than one-half acre and are contiguous to existing structures constructed below the RFE;
  3. Variances shall only be granted upon a showing of good and sufficient cause, shall be the minimum relief necessary, shall not cause increased risks to public safety or nuisances, shall not increase costs for rescue and relief efforts and shall not be contrary to the purpose of the ordinance.
- (c) A variance shall not
1. Grant, extend or increase any use prohibited in the zoning district.
  2. Be granted for a hardship based solely on an economic gain or loss.
  3. Be granted for a hardship, which is self-created.
  4. Damage the rights or property values of other persons in the area.
  5. Allow actions without the amendments to this ordinance or map(s) required in s. 20.37.
  6. Allow any alteration of an historic structure, including its use, which would preclude its continued designation as an historic structure.
- (d) When a floodplain variance is granted the Board shall notify the applicant in writing that it may increase flood insurance premiums and risks to life and property. Flood insurance premiums could increase \$25.00 per \$100.00 of coverage. A copy shall be maintained with the variance record.

**20.33 TO REVIEW APPEALS OF PERMIT DENIALS**

- (1) The Zoning Agency (s.20.31) or Board shall review all data related to the appeal. This may include:
  - (a) Permit application data listed in s. 20.30 (2).
  - (b) Floodway/floodfringe determination data in s. 20.24.
  - (c) Data listed in s. 20.14(1) (b) 2. where the applicant has not submitted this information to the zoning administrator.
  - (d) Other data submitted with the application, or submitted to the Board with the appeal.
- (2) For appeals of all denied permits the Board shall:
  - (a) Follow the procedures of s. 20.32;
  - (b) Consider zoning agency recommendations; and
  - (c) Either uphold the denial or grant the appeal.
- (3) For appeals concerning increases in regional flood elevation, the Board shall:
  - (a) Uphold the denial where the Board agrees with the data showing an increase in flood elevation. Increases may only be allowed after amending the flood profile and map and all appropriate legal arrangements are made with all adversely affected property owners as per the requirements of section 20.36 Amendments; and
  - (b) Grant the appeal where the Board agrees that the data properly demonstrates that the project does not cause an increase provided no other reasons for denial exist.

**20.34 FLOODPROOFING STANDARDS FOR NONCONFORMING STRUCTURE OR USES**

- (1) No permit or variance shall be issued for a non-residential structure designed to be watertight below the regional flood elevation until the applicant submits a plan certified by a registered professional engineer or architect that the floodproofing measures will protect the structure or development to the flood protection elevation and submits a FEMA Floodproofing Certificate.
  
- (2) For a structure designed to allow the entry of floodwaters, no permit or variance shall be issued until the applicant submits a plan either:
  - (a) Certified by a registered professional engineer or architect; or
  - (b) Meets or exceeds the following standards:
    1. A minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding;
    2. The bottom of all openings shall be no higher than one foot above grade; and
    3. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.
  
- (3) Floodproofing measures shall be designed, as appropriate, to:
  - (a) Withstand flood pressures, depths, velocities, uplift and impact forces and other regional flood factors;
  - (b) Protect structures to the flood protection elevation;
  - (c) Anchor structures to foundations to resist flotation and lateral movement;
  - (d) Minimize or eliminate infiltration of flood water; and
  - (e) Minimize or eliminate discharges into flood waters.

**20.35 PUBLIC INFORMATION**

- (1) Place marks on structures to show the depth of inundation during the regional flood.
- (2) All maps, engineering data and regulations shall be available and widely distributed.
- (3) All real estate transfers should show what floodplain zoning district any real property is in.

**20.36 AMENDMENTS**

Obstructions or increases may only be permitted if amendments are made to this ordinance, the official Floodplain Zoning Maps, floodway lines and water surface profiles, in accordance with section 20.37.

- (1) In AE zones with a mapped floodway, no obstructions or increases shall be permitted unless the applicant receives a Conditional Letter of Map Revision from FEMA and amendments are to this ordinance, the official Floodplain Zoning Maps, floodway lines and water surface profiles, in accordance with section 20.37. Any such alterations must be reviewed and approved by FEMA and the DNR.
- (2) In A zones, increases equal to or greater than 1.0 foot may only be permitted if the applicant receives a Conditional Letter of Map Revision from FEMA and amendments are made to this ordinance, the official Floodplain Zoning Maps, floodway lines, and water surface profiles, in accordance with section 20.37.

**20.37 GENERAL**

The governing body may change or supplement the floodplain zoning district boundaries and this ordinance in the manner provided by law. Actions that require an amendment include, but are not limited to, the following:

- (1) Any change to the floodplain boundaries and/or watercourse alterations on the FIRM.
- (2) Correction of discrepancies between the water surface profiles and floodplain zoning maps.
- (3) Any fill in the floodplain that raises the elevation of the filled area to a height at or above the flood protection elevation and is contiguous to land lying outside the floodplain.
- (4) Any fill or floodplain encroachment that obstructs flow causing any increase in the regional flood height.
- (5) Any upgrade to a floodplain zoning ordinance text required by s. NR 116.05, Wis. Adm. Code, or otherwise required by law, or for changes by the municipality.
- (6) All channel relocations and changes to the maps to alter floodway lines or to remove an area from the floodway or the floodfringe that is based on a base flood elevation from a FIRM requires prior approval by FEMA.
- (7) Any changes to any other floodplain maps listed in s. 20.05 (2) (b).

**Note:** Consult the FEMA web site - [www.fema.gov](http://www.fema.gov) - for a current map change fee schedule.

**20.38 PROCEDURES**

Ordinance amendments may be made upon petition of any interested party according to the provisions of s. 62.23, Stats. for cities and villages, or 59.69, Stats., for counties. Such petitions shall include all necessary data required by ss. 20.24 and 20.30 (2).

- (1) The proposed amendment shall be referred to the zoning agency for a public hearing and recommendation to the governing body. The amendment and notice of public hearing shall be submitted to the Department Regional office for review prior to the hearing. The amendment procedure shall comply with the provisions of s. 62.23, Stats. for cities and villages or s. 59.69,Stats., for counties.
- (2) No amendments shall become effective until reviewed and approved by the Department.
- (3) All persons petitioning for a map amendment that obstructs flow causing any increase in the regional flood height, shall obtain flooding easements or other appropriate legal arrangements from all adversely affected property owners and notify local units of government before the amendment can be approved by the governing body.
- (4) For amendments in areas with no water surface profiles, the zoning agency or board shall consider data submitted by the Department, the zoning administrator's visual on-site inspections and other available information. (See s. 20.05 (4).)
- (5) The land use permit shall not be issued until a letter of map revision is issued by FEMA for the proposed changes.

**20.39 ENFORCEMENT AND PENALTIES**

Any violation of the provisions of this ordinance by any person shall be unlawful and shall be referred to the municipal attorney who shall expeditiously prosecute all such violators. A violator shall, upon conviction, forfeit to the municipality a penalty of not less than \$ 10.00 and not more than \$ 50.00 per day, together with a taxable cost of such action. Each day of continued violation shall constitute a separate offense. Every violation of this ordinance is a public nuisance and the creation may be enjoined and the maintenance may be abated by action at suit of the municipality, the state, or any citizen thereof pursuant to s. 87.30, Stats.

**20.40 DEFINITIONS**

Unless specifically defined below, words and phrases used in this ordinance shall have the same meaning as they have at common law and to give this ordinance its most reasonable application. Words used in the present tense include the future, the singular number includes the plural and the plural number includes the singular. The word "may" is permissive; "shall" is mandatory and not discretionary.

**A ZONES.** Those areas shown on the Official Floodplain Zoning Map which would be inundated by the regional flood. These areas may be numbered or unnumbered A Zones. The A Zones may or may not be reflective of flood profiles, depending on the availability of data for a given area.

**AH ZONES.** See AREA OF SHALLOW FLOODING.

**AO ZONES.** See AREA OF SHALLOW FLOODING.

**ACCESSORY STRUCTURE OR USE.** A facility, structure, building or use which is accessory or incidental to the principal use of a property, structure or building.

**ALTERATION.** An enhancement, upgrading or substantial change or modification other than an addition or repair to a dwelling, or to electrical, plumbing, heating, ventilation, air conditioning and other systems within a structure.

**AREA OF SHALLOW FLOODING.** A designated AO, AH, AR/AO, AR/AH, or VO zone on a Community Flood Insurance Rate Map (FIRM) with a 1% or greater annual chance of flooding to an average depth of 1 to 3 feet where a clearly defined channel does not exist, where the path of flooding is unpredictable, and where velocity flood may be evident. Such flooding is characterized by ponding or sheet flow.

**BASE FLOOD.** Means the flood having a one percent chance of being equaled or exceeded in any given year, as published by FEMA as part of a FIS and depicted on a FIRM.

**BASEMENT.** Any enclosed area of a building having its floor subgrade, i.e., below ground level, on all sides.

**BUILDING.** See STRUCTURE.

**BULKHEAD LINE.** A geographic line along a reach of navigable water that has been adopted by a municipal ordinance and approved by the Department pursuant to s. 30.11, Stats. and which allows limited filling between this bulkhead line and the original ordinary high water mark, except where such filling is prohibited by the floodway provisions of this ordinance.

**CAMPGROUND.** Any parcel of land which is designed, maintained, intended or used for the purpose of providing sites for nonpermanent overnight use by 4 or more camping units, or which is advertised or represented as a camping area.

**CAMPING UNIT.** Any portable device, no more than 400 square feet in area, used as a temporary shelter, including but not limited to a camping trailer, motor home, bus, van, pick-up truck or tent that is fully licensed, if required, and ready for highway use.

**CERTIFICATE OF COMPLIANCE.** A certification that the construction and the use of land or a building, the elevation of fill or the lowest floor of a structure is in compliance with all of the provisions of this ordinance.

**CHANNEL.** A natural or artificial watercourse with definite bed and banks to confine and conduct normal flow of water.

**CRAWLWAYS OR CRAWL SPACE.** An enclosed area below the first usable floor of a building, generally less than five (5) feet in height, used for limited access to plumbing and electrical utilities.

**DECK.** An unenclosed exterior structure that has no roof or sides, but has a permeable floor which allows the infiltration of precipitation.

**DEPARTMENT.** The Wisconsin Department of Natural Resources.

**DEVELOPMENT.** Any artificial change to improved or unimproved real estate, including, but not limited to, the construction of buildings, structures or accessory structures; the construction of additions or alterations to buildings, structures or accessory structures; the repair of any damaged structure or the improvement or renovation of any structure, regardless of percentage of damage or improvement; the placement of buildings or structures; mining, dredging, filling, grading, paving, excavation or drilling operations; the storage, deposition or extraction of materials or equipment; and the installation, repair or removal of public or private sewage disposal systems or water supply facilities.

**DRYLAND ACCESS.** A vehicular access route which is above the regional flood elevation and which connects land located in the floodplain to land outside the floodplain, such as a road with its surface above regional flood elevation and wide enough for wheeled rescue and relief vehicles.

**ENCROACHMENT.** Any fill, structure, equipment, building, use or development in the floodway.

**FEDERAL EMERGENCY MANAGEMENT AGENCY (FEMA).** The federal agency that administers the National Flood Insurance Program.

**FLOOD INSURANCE RATE MAP (FIRM).** A map of a community on which the Federal Insurance Administration has delineated both special flood hazard areas (the floodplain) and the risk premium zones applicable to the community. This map can only be amended by the Federal Emergency Management Agency.

FLOOD or "FLOODING. A general and temporary condition of partial or complete inundation of normally dry land areas caused by one of the following conditions:

- ✓ The overflow or rise of inland waters,
- ✓ The rapid accumulation or runoff of surface waters from any source,
- ✓ The inundation caused by waves or currents of water exceeding anticipated cyclical levels along the shore of Lake Michigan or Lake Superior, or
- ✓ The sudden increase caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as a seiche, or by some similarly unusual event.

FLOOD FREQUENCY. The probability of a flood occurrence which is determined from statistical analyses. The frequency of a particular flood event is usually expressed as occurring, on the average, once in a specified number of years or as a percent (%) chance of occurring in any given year.

FLOODFRINGE. That portion of the floodplain outside of the floodway which is covered by floodwaters during the regional flood and associated with standing water rather than flowing water.

FLOOD HAZARD BOUNDARY MAP. A map designating approximate flood hazard areas. Flood hazard areas are designated as unnumbered A-Zones and do not contain floodway lines or regional flood elevations. This map forms the basis for both the regulatory and insurance aspects of the National Flood Insurance Program (NFIP) until superseded by a Flood Insurance Study and a Flood Insurance Rate Map.

**FLOOD INSURANCE STUDY.** A technical engineering examination, evaluation, and determination of the local flood hazard areas. It provides maps designating those areas affected by the regional flood and provides both flood insurance rate zones and base flood elevations and may provide floodway lines. The flood hazard areas are designated as numbered and unnumbered A-Zones. Flood Insurance Rate Maps, that accompany the Flood Insurance Study, form the basis for both the regulatory and the insurance aspects of the National Flood Insurance Program.

**FLOODPLAIN.** Land which has been or may be covered by flood water during the regional flood. It includes the floodway and the floodfringe, and may include other designated floodplain areas for regulatory purposes.

**FLOODPLAIN ISLAND.** A natural geologic land formation within the floodplain that is surrounded, but not covered, by floodwater during the regional flood.

**FLOODPLAIN MANAGEMENT.** Policy and procedures to insure wise use of floodplains, including mapping and engineering, mitigation, education, and administration and enforcement of floodplain regulations.

**FLOOD PROFILE.** A graph or a longitudinal profile line showing the relationship of the water surface elevation of a flood event to locations of land surface elevations along a stream or river.

**FLOODPROOFING.** Any combination of structural provisions, changes or adjustments to properties and structures, water and sanitary facilities and contents of buildings subject to flooding, for the purpose of reducing or eliminating flood damage.

**FLOOD PROTECTION ELEVATION.** An elevation of two feet of freeboard above the water surface profile elevation designated for the regional flood. (Also see: FREEBOARD.)

**FLOOD STORAGE.** Those floodplain areas where storage of floodwaters has been taken into account during analysis in reducing the regional flood discharge.

**FLOODWAY.** The channel of a river or stream and those portions of the floodplain adjoining the channel required to carry the regional flood discharge.

**FREEBOARD.** A safety factor expressed in terms of a specified number of feet above a calculated flood level. Freeboard compensates for any factors that cause flood heights greater than those calculated, including ice jams, debris accumulation, wave action, obstruction of bridge openings and floodways, the effects of watershed urbanization, loss of flood storage areas due to development and aggregation of the river or stream bed.

**HABITABLE STRUCTURE.** Any structure or portion thereof used or designed for human habitation.

**HEARING NOTICE.** Publication or posting meeting the requirements of Ch. 985, Stats. For appeals, a Class 1 notice, published once at least one week (7 days) before the hearing, is required. For all zoning ordinances and amendments, a Class 2 notice, published twice, once each week consecutively, the last at least a week (7 days) before the hearing. Local ordinances or bylaws may require additional notice, exceeding these minimums.

**HIGH FLOOD DAMAGE POTENTIAL.** Damage that could result from flooding that includes any danger to life or health or any significant economic loss to a structure or building and its contents.

**HIGHEST ADJACENT GRADE.** The highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

**HISTORIC STRUCTURE.** Any structure that is either:

- ✓ Listed individually in the National Register of Historic Places or preliminarily determined by the Secretary of the Interior as meeting the requirements for listing on the National Register,
- ✓ Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district,
- ✓ Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior, or
- ✓ Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either by an approved state program, as determined by the Secretary of the Interior; or by the Secretary of the Interior in states without approved programs.

**INCREASE IN REGIONAL FLOOD HEIGHT.** A calculated upward rise in the regional flood elevation, equal to or greater than 0.01 foot, based on a comparison of existing conditions and proposed conditions, which is directly attributable to development in the floodplain but not attributable to manipulation of mathematical variables such as roughness factors, expansion and contraction coefficients and discharge.

**LAND USE.** Any nonstructural use made of unimproved or improved real estate. (Also see DEVELOPMENT.)

**LOWEST ADJACENT GRADE.** Elevation of the lowest ground surface that touches any of the exterior walls of a building.

**LOWEST FLOOR.** The lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access, or storage in an area other than a basement area is not considered a buildings lowest floor; provided that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of 44 CFR 60.3.

**MAINTENANCE.** The act or process of restoring to original soundness, including redecorating, refinishing, non-structural repairs or the replacement of existing fixtures, systems or equipment with the equivalent fixtures, systems or structures.

**MANUFACTURED HOME.** A structure transportable in one or more sections, which is built on a permanent chassis and is designed to be used with or without a permanent foundation when connected to required utilities. The term "manufactured home" includes a mobile home but does not include a "mobile recreational vehicle."

**MOBILE/MANUFACTURED HOME PARK OR SUBDIVISION.** A parcel (or contiguous parcels) of land, divided into two or more manufactured home lots for rent or sale.

**MOBILE/MANUFACTURED HOME PARK OR SUBDIVISION EXISTING.** A parcel of land, divided into two or more manufactured home lots for rent or sale, on which the construction of facilities for servicing the lots is completed before the effective date of this ordinance. At a minimum, this would include the installation of utilities, the construction of streets and either final grading or the pouring of concrete pads.

**MOBILE/MANUFACTURED HOME PARK, EXPANSION TO EXISTING.** The preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed. This includes installation of utilities, construction of streets and either final site grading, or the pouring of concrete pads.

**MOBILE RECREATIONAL VEHICLE.** A vehicle which is built on a single chassis, 400 square feet or less when measured at the largest horizontal projection, designed to be self-propelled, carried or permanently towable by a licensed, light-duty vehicle, is licensed for highway use if registration is required and is designed primarily not for use as a permanent dwelling, but as temporary living quarters for recreational, camping, travel or seasonal use. Manufactured homes that are towed or carried on to a parcel of land, but do not remain capable of being towed or carried, including park model homes, do not fall within the definition of mobile recreational vehicles.

**MODEL, CORRECTED EFFECTIVE.** A hydraulic engineering model that corrects any errors that occur in the Duplicate Effective Model, adds any additional cross-sections to the Duplicate Effective Model, or incorporates more detailed topographic information than that used in the current effective model.

**MODEL, DUPLICATE EFFECTIVE.** A copy of the hydraulic analysis used in the effective FIS and referred to as the effective model.

**MODEL, EFFECTIVE.** The hydraulic engineering model that was used to produce the current effective Flood Insurance Study.

**MODEL, EXISTING (PRE-PROJECT).** A modification of the Duplicate Effective Model or Corrective Effective Model to reflect any man-made modifications that have occurred within the floodplain since the date of the effective model but prior to the construction of the project for which the revision is being requested. If no modification has occurred since the date of the effective model, then this model would be identical to the corrected effective model or duplicate effective model.

**MODEL, REVISED (POST-PROJECT).** A modification of the existing or pre-project conditions model, duplicate effective model or corrected effective model to reflect revised or post-project condition.

**MUNICIPALITY or MUNICIPAL.** The county, city or village governmental units enacting, administering and enforcing this zoning ordinance.

**NAVD or NORTH AMERICAN VERTICAL DATUM.** Elevations referenced to mean sea level datums, 1988 adjustment.

**NGVD or NATIONAL GEODETIC VERTICAL DATUM.** Elevations referenced to mean sea level datum, 1929 adjustment.

**NEW CONSTRUCTION.** For floodplain management purposes, "new construction" means structures for which the start of construction commenced on or after the effective date of floodplain zoning regulations adopted by this community and includes any subsequent improvements to such structures. For the purpose of determining flood insurance rates, it includes any structures for which the "start of construction" commenced on or after the effective date of an initial FIRM or after December 31, 1974, whichever is later, and includes any subsequent improvements to such structures.

**NONCONFORMING STRUCTURE.** An existing lawful structure or building which is not in conformity with the dimensional or structural requirements of this ordinance for the area of the floodplain, which it occupies. (For example, an existing residential structure in the floodfringe district is a conforming use. However, if the lowest floor is lower than the flood protection elevation, the structure is nonconforming.)

**NONCONFORMING USE.** An existing lawful use or accessory use of a structure or building which is not in conformity with the provisions of this ordinance for the area of the floodplain which it occupies. (Such as a residence in the floodway.)

**OBSTRUCTION TO FLOW.** Any development which blocks the conveyance of floodwaters such that this development alone or together with any future development will cause an increase in regional flood height.

**OFFICIAL FLOODPLAIN ZONING MAP.** That map, adopted and made part of this, as described in s. 1.5(2), which has been approved by the Department and FEMA.

**OPEN SPACE USE.** Those uses having a relatively low flood damage potential and not involving structures.

**ORDINARY HIGHWATER MARK.** The point on the bank or shore up to which the presence and action of surface water is so continuous as to leave a distinctive mark such as by erosion, destruction or prevention of terrestrial vegetation, predominance of aquatic vegetation, or other easily recognized characteristic.

**PERSON.** An individual, or group of individuals, corporation, partnership, association, municipality or state agency.

**PRIVATE SEWAGE SYSTEM.** A sewage treatment and disposal system serving one structure with a septic tank and soil absorption field located on the same parcel as the structure. It also means an alternative sewage system approved by the Department of Safety and Professional Services, including a substitute for the septic tank or soil absorption field, a holding tank, a system serving more than one structure or a system located on a different parcel than the structure.

**PUBLIC UTILITIES.** Those utilities using underground or overhead transmission lines such as electric, telephone and telegraph, and distribution and collection systems such as water, sanitary sewer and storm sewer.

**REASONABLY SAFE FROM FLOODING.** Means base flood waters will not inundate the land or damage structures to be removed from the special flood hazard area and that any subsurface waters related to the base flood will not damage existing or proposed buildings.

**REGIONAL FLOOD.** A flood determined to be representative of large floods known to have occurred in Wisconsin. A regional flood is a flood with a one percent chance of being equaled or exceeded in any given year, and if depicted on the FIRM, the RFE is equivalent to the BFE.

**START OF CONSTRUCTION.** The date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond initial excavation, or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling, nor does it include the installation of streets and/or walkways, nor does it include excavation for a basement, footings, piers or foundations or the erection of temporary forms, nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For an alteration, the actual start of construction means the first alteration of any wall, ceiling, floor or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

**STRUCTURE.** Any manmade object with form, shape and utility, either permanently or temporarily attached to, placed upon or set into the ground, stream bed or lake bed, including, but not limited to, roofed and walled buildings, gas or liquid storage tanks, bridges, dams and culverts.

**SUBDIVISION.** Has the meaning given in ss. 236.02 (12) Wis. Stats.

**SUBSTANTIAL DAMAGE.** Damage of any origin sustained by a structure, whereby the cost of restoring the structure to its pre-damaged condition would equal or exceed 50 percent of the equalized assessed value of the structure before the damage occurred.

**SUBSTANTIAL IMPROVEMENT.** Any repair, reconstruction, rehabilitation, addition or improvement of a building or structure, the cost of which equals or exceeds 50 % of the equalized assessed value of the structure before the improvement or repair is started. If the structure has sustained substantial damage, any repairs are considered substantial improvements regardless of the work performed. The term does not however, include either any project for the improvement of a building required to correct existing health, sanitary or safety code violations identified by the building official and that are minimum necessary to assure safe living conditions, or any alterations of a historic structure provided that the alteration will not preclude the structures continued designation as a historic structure.

**UNNECESSARY HARDSHIP.** Where special conditions affecting a particular property, which were not self-created, have made strict conformity with restrictions governing areas, setbacks, frontage, height or density unnecessarily burdensome or unreasonable in light of the purposes of the ordinance.

**VARIANCE.** An authorization by the board of adjustment or appeals for the construction or maintenance of a building or structure in a manner that is inconsistent with dimensional standards (not uses) contained in the floodplain zoning ordinance.

**VIOLATION.** The failure of a structure or other development to be fully compliant with the floodplain zoning ordinance. A structure or other development without required permits, lowest floor elevation documentation, flood proofing certificates or required floodway encroachment calculations is presumed to be in violation until such time as that documentation is provided.

**WATERSHED.** The entire region contributing runoff or surface water to a watercourse or body of water.

**WATER SURFACE PROFILE.** A graphical representation showing the elevation of the water surface of a watercourse for each position along a reach of river or stream at a certain flood flow. A water surface profile of the regional flood is used in regulating floodplain areas.

**WELL.** Means an excavation opening in the ground made by digging, boring, drilling, driving or other methods, to obtain groundwater regardless of its intended use.